



AMERICAN CAR CRAFT INSTRUCTIONS

2007-2018 Jeep Wrangler JK & JKU - Tail Light Covers US Safari Style 2pc | Black Powder Coated/Brushed Stainless Steel

SKU #142093/142094



Included:

2-Tail Light Covers

Please check local highway laws before use.

Liner Info: Your new accessories will come to you with a protective surface liner. Leave this liner in place until the installation is complete to prevent fingerprints and or possible scratches during installation. This liner is required to remain on the part until you are instructed to remove it.

1. Clean the area for the easiest installation. Remove any dirt, grime, dust, or debris that needs to be removed. We always recommend using some rubbing alcohol and then drying the area for a final 'cleanse.'
2. Remove the factory screws (keep these; you will need them for installation), paying special attention to which screws came out of what side of the tail light (the longer ones should be on the outside, while the shorter ones are closer to the inner part of the Jeep). **Note:** Do not remove the light itself, as this is not necessary.
3. Once you are ready, take your tail light cover, and remove the protective surface liner that is on it.
4. Take factory screws and thread them through the holes in your new tail light covers and reattach, drilling them in until the part is secure. Be sure to insert the correct, corresponding length of screws on either side (shorter length toward the inside, longer length towards the outside).
5. That's all!

Thank you and enjoy your purchase!

**If any questions occur during installation, please contact
AMERICAN CAR CRAFT**

18924 SAKERA ROAD-HUDSON FLORIDA 34667

Phone # 727-861-1500

Fax # 727-861-1520 www.americancarcraft.com