



413 West Elm Street • Sycamore, IL 60178
(866)248-6357 • (815)895-6786

www.autometer.com • service@autometer.com

DEDENBEAR DELAY BOX INSTALLATION KIT • Model IK

In this installation, the transbrake will be delayed only when the SAFETY SWITCH (Bypass Switch) is in the "Delay" mode. Please set the switch to "No Delay" (bypass) at all times except when you are on the track. Use the 15 ft. of 12-GAUGE wire for main power from Master ON-OFF.

NOTE: THE OPTIONAL "LINE LOCK" TERMINAL WILL ALWAYS BE DELAYED THE AMOUNT SHOWN ON THE DELAY BOX. NO MATTER WHERE THE SAFETY SWITCH IS SET!

(If you need a Bypass switch to control both the Transbrake & Line Lock terminal, a special double pole toggle is available, p/n TSWDPRTD \$15)

The Safety Switch (Bypass Switch) provides you with true absolute 0.000 seconds delay, and bypasses the delay box completely!

- KIT INCLUDES:**
- (1) Precision Transbrake Button
 - (1) 14 gauge H.D. Stretch Cord
 - (1) 15 ft 12 gauge wire - RED
 - (4) 10 ft. ea. 14 gauge wire - BLUE, YELLOW, GREEN, BLACK
 - (25) Nylon Wire Ties
 - (5) #6 Sheet metal screws
 - (4) 1/4" flat washers
 - (1) Serrated washer
 - (6) Ring terminals
 - (1) Pair 1/4" Quick Disconnects
 - (3) Butt Connectors
 - (1) In-Line fuse holder w/ fuse

