



413 West Elm Street • Sycamore, IL 60178
(866)248-6357 • (815)895-6786
www.autometer.com • service@autometer.com


INSTALLATION

- 1) Remove the carburetor, gasket, and mounting studs.
- 2) Install four carb studs of an appropriate length to mount the throttle stop, carburetor, and any spacers or heat shields.
- 3) Install an open or four hole gasket on the intake, any spacers or heat shields, then the throttle stop. The throttle stop can be mounted with the adjustment knob on either the driver or passenger side of the motor. If you decide to mount the stop with the adjustment knob on the passenger side, test fit the carb by gently setting the carb on the stop and checking for interference or clearance problems with the fuel lines.
- 4) A four hole gasket is recommended between the throttle stop and the carburetor, and any open spacers or gaskets should be avoided between the carb and throttle stop.
- 5) Reinstall the carburetor, fuel lines, carb linkage and air pan / air cleaner.

OPERATION

The manual disc stop's throttle position is adjusted by threading the adjustment knob in or out. Threading in the knob will increase the opening size (raising RPM while on the stop) and threading out the knob will decrease the opening size (lowering RPM while on the stop). Make sure to tighten the locknut after adjustments.

TIP: The most accurate way to make changes to your throttle position is to use a pair of dial calipers to measure the distance between the adjustment knob and the machined casting surface. Keep this measurement in your log book for future reference.



LIMITED 1 YEAR WARRANTY

DEDENBEAR Products, Inc. warrants to the consumer that all DEDENBEAR Products purchased from an Authorized DEDENBEAR Reseller will be free from defects in material and workmanship for a period of twelve (12) months from date of the original purchase. Products that fail within this 12 month warranty period will be repaired or replaced at DEDENBEAR's option, when determined by DEDENBEAR that the product failed due to defects in material or workmanship. This warranty is limited to the repair or replacement of parts in the DEDENBEAR Product and the necessary labor done by DEDENBEAR to effect the repair or replacement of the DEDENBEAR product. In no event shall DEDENBEAR's cost to repair or replace a DEDENBEAR under this warranty exceed the original purchase price of the DEDENBEAR Product. Nor shall DEDENBEAR Products, Inc. be responsible for special, incidental or consequential damages or costs incurred due to the failure of a DEDENBEAR Product. This warranty applies only to the original purchaser of the DEDENBEAR Product and is non-transferable. This warranty also applies only to DEDENBEAR Products purchased from an Authorized DEDENBEAR Reseller. All implied warranties shall be limited in duration to the said 12 month warranty period. Breaking the instrument seal, improper use or installation, accident, water damage, abuse, unauthorized repairs or alterations voids this warranty. DEDENBEAR disclaims any liability for consequential damages due to the breach of any written or implied warranty on all products manufactured by DEDENBEAR Products, Inc.

FOR SERVICE SEND TO: DEDENBEAR PRODUCTS, INC 413 W. Elm St. Sycamore, IL 60178 USA (866) 248-6357
Email: service@autometer.com

CUSTOMER SERVICE & TECH. SUPPORT: (866)248-6357 Mon-Fri 8am-5pm CST