



PART # 69280, 69281 & 69287 - Standard
PART # 69286, 61286 & 66287 - HTC
PART # 69288, 61288 & 69887 - ELITE
INSTRUCTION SHEET
BB CHEVY TRUCK 1/2 & 3/4 TON 4x4

CAUTION! This is a custom designed exhaust header system, designed for this particular application (s). Do not bend, bang, cut, dent, drill or heat any portion of this header! Any alteration other than those suggested in this instruction sheet will void the Hedman Lifetime Guarantee!
 To prevent leaks, install your headers using Hedman Hedders exhaust gaskets ONLY and a spray copper gasket sealant.

BEFORE STARTING INSTALLATION:
 It is necessary to raise the vehicle at least 36 inches from the ground. A floor hoist is recommended, if not available, use a hydraulic floor jack with jack stands. **DO NOT USE A BUMPER JACK!**

PRE-INSTALLATION:

1. Disconnect battery and remove spark plugs (Number Wires).
2. Remove oil dip stick tube, disconnect A/C bracket. Disconnect oil plug wire and move aside.
3. Remove stock exhaust head pipes and stock exhaust manifold.

INSTALLATION INSTRUCTIONS:

RIGHT SIDE:

1. Unbolt motor mount bolt, raise engine using 2 small blocks of wood between hydraulic floor jack & oil pan, approx. 1 or 2 inches.
2. With gasket in place install header from below, start all bolts. **DO NOT TIGHTEN!**
3. Lower engine, re-install motor mount bolt and tighten, re-route starter cable and be sure that there is adequate clearance of all hoses, lines, wires etc. Tighten header bolts evenly.

LEFT SIDE:


1. With gasket in place, install header from bottom of engine, start all bolts and tighten evenly.
2. Re-install oil dip stick tube, spark plugs, re-connect oil plug wire, and all parts that have been removed or disconnected. (On some models a shorter oil filter must be used.)
3. Bolt steel hook-up cones and connect to your muffler system.
4. Re-connect battery.
5. Start engine, test drive vehicle allowing engine to gain normal operating temperature. Check for leaks and new or unusual noises. After test drive is completed, re-tighten Header bolts.

ENJOY YOUR HEADERS WHILE COMBINING INCREASED FUEL ECONOMY WITH BETTER PERFORMANCE.

SPECIAL INSTRUCTIONS!

After installing your headers it is very important that your exhaust system be suspended properly. As indicated in the drawing below you must place hangers as close to the header collector as possible. Rubber hangers should be used to allow the front of the system to flex with the engine torque. A hanger is needed before and after the muffler (s). When your exhaust system is unbolted from the header collector, it should remain suspended all by itself. Your Headers Are Not designed to support your exhaust system. Failure to follow these instructions will most likely result in cracks around the area where your primary tubes and collector are welded together, and will nullify your "Lifetime Guarantee".

DO NOT WRAP YOUR NEW HEADERS!
 The use of thermal wraps will drastically shorten the life of your Headers, and will void the Hedman "Lifetime Guarantee".



WARNING: Not applicable or intended for street or highway use. Legal only for racing vehicles which may never be used upon a public highway.

12438 Putnam Street • Whittier, CA 90602 • tel (562) 921-0404 • fax (562) 921-7515
 website: www.hedman.com • email: techsupport@hedman.com