

# Product information

## Top Tec 4200 SAE 5W-30

PI 76/21/08/2020



### Description

Modern fully synthetic, low-SAPS motor oil for superior performance and long engine life. Designed for use in numerous Volkswagen and Audi vehicles and also suitable for use in a variety of BMW and Mercedes-Benz diesel vehicles as well as specific Porsche models, etc. Use with extended oil change intervals as per manufacturer.

### Properties

- compatible for the use with turbochargers and catalytic converters
- reduces pollutant emissions
- smooth engine running
- reduces fuel consumption
- instant lubrication after cold start
- for extended service intervals
- excellent wear resistance
- optimum oil pressure under all operating conditions
- outstanding engine cleanliness
- high lubrication reliability
- optimum stability to aging
- high shear stability

### Specifications and approvals:

ACEA C3 • API SP • BMW Longlife-04 • MB-Approval 229.31 • MB-Approval 229.51 • Porsche C30 • VW 504 00 • VW 507 00

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

ACEA C2 • BMW Longlife-01 (up to 2018)\* • BMW Longlife-01 FE (up to 2018)\* • Fiat 9.55535-S1 • Fiat 9.55535-S3 • VW 500 00 • VW 501 01 • VW 502 00 • VW 503 00 • VW 503 01 • VW 505 00 • VW 505 01 • VW 506 00 • VW 506 01 (With the exception of R5 and V10 TDI engines before 6/2006) • \*limited to BMW gasoline engines without particle filters in the EU including Norway, Switzerland and Liechtenstein

### Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 59 °F	0,855 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	70,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	12,2 mm <sup>2</sup> /s ASTM D 7042-04



### Technical data

Viscosity at -31 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -22 °F (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	173 DIN ISO 2909
HTHS at 302 °F	≥ 3,5 mPas ASTM D5481
Pour point	-44 °F DIN ISO 3016
Evaporation loss (Noack)	9,5 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	8,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

### Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

### Application

Observe the manufacturers instructions!

### Available pack sizes

1 l Canister plastic	2004 USA AND CANADA (-EN-F-)
5 l Canister plastic	2011 USA AND CANADA (-EN-F-)
20 l Canister plastic	20125 USA AND CANADA (-EN-F-)

# Product information

PI 76/21/08/2020



## Top Tec 4200 SAE 5W-30

### Available pack sizes

60 l Drum sheet metal	22086 USA AND CANADA (-EN- F-)
205 l Drum sheet metal	22087 USA AND CANADA (-EN- F-)
1000 l Container	3716 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**