

HEADER INSTALLATION INSTRUCTIONS APPLICATION 1979-1993 FORD Mustang, 255-302W PART NUMBER: D6671



WARNING: These headers are legal for Off Highway use (except in California or states that have adopted California emission standards) or Racing use (which may never be used on a Highway), or for use on pre emission controlled motor vehicles/motor vehicle engines (pre 1966 domestic vehicles certified to California standards, pre 1968 domestic vehicles certified to Federal standards and all pre 1968 Foreign vehicles) **Only**.

PerTronix® thanks you for choosing **DOUG'S HEADERS**, the best fitting, highest quality header on the market. In order to realize the full potential of our good fit, please read and understand these instructions completely prior to starting work.

CHECK TO MAKE SURE YOU RECEIVED THE PROPER PARTS FOR YOUR APPLICATION. THE HEADER NUMBER WILL BE STAMPED ON THE ENGINE FLANGE. IF YOU ARE UNSURE YOU HAVE RECEIVED THE PROPER PARTS CALL BEFORE YOU START WORK.

BE SURE TO WORK SAFE! WHENEVER YOU WORK UNDER THE VEHICLE BE SURE THAT IT IS LOCATED ON LEVEL, SOLID GROUND AND IS SUPPORTED BY ADEQUATE SAFETY STANDS!

REMEMBER: HOT ASPHALT WILL NOT SUPPORT MOST JACK STANDS!

Many factors affect the installation of headers, some of which are broken or aftermarket motor mounts, accidents that impact the configuration of the frame, and/or the installation of different engines or aftermarket cylinder heads. Most installations require some welding. If you are uncomfortable with welding operations, we recommend that you contact a professional exhaust system specialist to install your new headers.

Attention Customers breaking in new engines: Due to the extreme heat generated during the break-in process, the appearance of the ceramic coating may be altered in certain areas. The protection characteristics and thermal barrier properties of the coating is never compromised. It is recommended that a cast iron manifold or old set of headers be used for this process.

Notice: The coating of these headers can be marred or scratched during installation. If the header needs to be returned and is damaged, you will be charged for recoat.

Note: The installation of this header requires that you use factory "Dual Hump" transmission crossmember, which came on '86-'89 Mustang 5.0 Liter models.



These Headers utilize two Slip Tubes on each side. Doug's only makes a partial cut through the flange during manufacturing and the customer MUST Cut the Flange the rest of the way in order to install these headers

DISASSEMBLY

1. Disconnect the negative battery cable from the battery.
2. If a car lift is not available, raise the vehicle 2 feet or higher and support it with adequate safety stands. Make sure the vehicle is on a flat solid surface and is stable.
3. Apply penetrating oil to all nuts and bolts to be removed.
4. Remove the air inlet assembly, diverter valve, hoses and oil dipstick tube.
5. Remove O² sensors, if so equipped.
6. Unbolt head pipes from stock exhaust manifolds.
7. Remove spark plugs, stock exhaust manifolds.
8. Replace the spark plugs finger tight so debris will not get into the cylinders while cleaning the head surface.
9. Clean the cylinder head surface which mates to the header. Use a gasket scraper and wire brush to make sure that the surface is absolutely clean.
10. After cleaning is complete remove the spark plugs again.

ASSEMBLY

1. Apply anti-seize to all header bolts being used.
2. Apply a **THIN** film of Ultra Copper Hi-Temp Sensor-Safe Silicone Sealer to the header side of the 2 supplied gaskets and glue them to the headers. Masking tape can be used to help stick the gasket to the manifold.
3. Apply a **THIN** film of Ultra Copper Hi-Temp Sensor-Safe Silicone Sealer to the engine side of the header gaskets.
4. If not using the O² sensors, screw in the provided plugs.
5. Note: C-6/A40D Transmission only – Trim the ear on the right side of the transmission bell housing (above the starter).
6. Starting from below, work the main header section up into place. Note: On some applications, it may be necessary to loosen the transmission mount bolts and move the engine/transmission aside for installation.
7. Start the header bolts but leave them loose.
8. Apply a small amount of **THIN** film of Ultra Copper Hi-Temp Sensor-Safe Silicone Sealer to the slip joints.
9. From above, install the remaining header tubes and bolts. Note: carefully bend/move the brake line to clear the tube for the #8 cylinder.
10. Tighten all bolts evenly.
11. Re-install engine oil dipstick tube and dipstick. Note: It may be necessary to bend the dipstick tube in order to clear the headers and line up with the mounting tab.
12. Install the diverter valve, hoses and air inlet assembly.
13. Tighten the header bolts evenly to a final torque of approximately 25 ft. lbs.
14. Reinstall spark plugs and plug wires.
15. Install reducers and attach exhaust system to reducers.
16. Install O² sensors, if so equipped.
17. Make sure all of the other fasteners are tightened.
18. Connect the negative battery cable.

IMPORTANT CHECK LIST

- Be sure that all brake lines and fuel lines are clear of headers and/or connector pipes.
- All spark plug wires, battery cables, or other electrical components should be clear of headers and/or connector pipes.
- If removed, make sure the dipstick is installed properly and that it has been replaced.
- Double-check the tightness of all bolts including brackets and accessories.
- Perform these checks again after the first 1000 miles.
- Check clearance and tightness of front driveshaft.

START THE ENGINE

Start the engine and allow it to warm up to operating temperature.

Caution! Hot parts! Wear protective clothing as needed.

Check for any unusual noises or exhaust leaks. If every thing is OK, stop the engine and tighten all bolts while the engine is still warm.

NOTE: Check the bolts periodically to make sure they have not loosened. Re-tighten after the first 500 miles and then again at 1000 miles.

PARTS LIST

Qty.	Description
1	Right side header
1	Left side header
2	Header gaskets
2	Collector gaskets
2	Reducers
2	O ² sensor plugs
1	Decal: DOUG'S HEADERS
1	Hardware kit:
16	3/8"-16 x 1" flanged header bolts
22	3/8" lock-washer
6	3/8"-16 x 1-1/4" hex bolts
6	3/8" hex nuts